Overview: model class G-CLASSIC-30

Safe and approved storage of flammable or toxic gases in working areas – for up to 4 x 50-litre gas cylinders



Proven technology

• G-CLASSIC-30 gas cylinder cabinets convince due to proven technology

Storage directly in the working area

• safe storage of gas cylinders directly in the working area – 30 minutes fire resistance

Further features of this model class



Locking

- doors lockable with profile cylinder lock
- cabinets can be integrated by the customer in an existing master key system



Pipe lead-throughs

- large area for flexible lead-through possibilities on the top of the cabinet
- no additional insulation of piping necessary



Comfortable adjusting possibilities

• integrated adjusting aids in the cabinet base ensure a fast and effective compensation for uneven floor of up to 10 mm

Possible interior equipment



· standard interior equipment complete with mounting rails, cylinder retainer and matching tension belts and rolling ramp



• lateral cylinder retainer for two 10-litre cylinders, alternatively in height-adjustable version (no tools required)



shelves in different versions



Safety storage cabinets for the storage of pressurised gas cylinders in working areas according to EN 14470-2 and TRGS 510











• **fire resistance 30 minutes** (type G30), type-tested in accordance with EN 14470-2



- excellent products with special manufacturer warranty
- extended manufacturer warranty of up to 5 years in combination with the asecos BASICPlus tariff







G-CLASSIC-30 **◆ 140 / 120 cm ▶**























Gas cylinder cabinet G-CLASSIC-30 model G30.205.140

in Light grey (RAL 7035), interior equipment with 1 x standard interior equipment for gas cylinders (sheet steel galvanised and powder coated)

Order No. 30651-001-30652 4

Technical data		G30.205.140
External dimensions W x D x H Internal dimensions W x D x H Weight without interior equip. Extraction air Air change 10 times Diff. pressure (air change 10 times) Air change 120 times Diff. pressure (air change 120 times) Distributed load Maximum load	mm mm kg DN m³/h Pa m³/h Pa kg/m²	1398 x 616 x 2050 1294 x 479 x 1874 545 75 12 5 139 143 Pa 507 600
50-litre gas cylinders	piece	4

Technical data		G30.205.120
External dimensions W x D x H Internal dimensions W x D x H Weight without interior equip. Extraction air Air change 10 times Diff. pressure (air change 10 times) Air change 120 times Diff. pressure (air change 120 times) Distributed load	mm mm kg DN m³/h Pa m³/h Pa kg/m²	1198 x 616 x 2050 1094 x 479 x 1874 485 75 10 5 118 103 Pa 560
Maximum load 50-litre gas cylinders	kg piece	600 4

Safe and approved storage of flammable or toxic gases in working areas - for up to 4 x 50-litre gas cylinders

Function / construction:

- no unauthorised use: doors lockable with profile cylinder (integration in an existing locking system possible)
- easy alignment: adjusting aids to compensate for uneven
- easy mounting of connecting pipes and gas fittings: large interior height (1890 mm), many lead-through possibilities on the top of the cabinet
- ventilation: integrated air ducts ready for connection (DN 75) to a technical exhaust, even ventilation inside the cabinet

Available equipment

- standard interior equipment complete with mounting rails, rolling ramp, cylinder retainer and matching tension belts
- lateral cylinder retainer for two 10-litre cylinders, alternatively in height adjustable version (no tools required)
- cylinder retainer across the entire width of the cabinet











Gas cylinder cabinet G-CLASSIC-30 model G30.205.120

in Light grey (RAL 7035), interior equipment with 1 x standard interior equipment for gas cylinders (sheet steel galvanised and powder coated)


Order No. 30663-001-30664 4


(lateral cylinder retainer optional)



G-CLASSIC-30 **◆ 140 / 120 cm ▶**








Exhaust air DN 75 fresh air Ø75 230 (72x / 60x) -1301 / 1201 180° Mat. 1800

Top view



Order example - how to order correctly








2 door colours are available at no extra cost:





7035	1004
001	002
Ⅲ M	odel
G30 205	140



^{*} W x D usable storage space / 1) load capacity (kg), 2) capacity (litres), 3) maximum container volume inside the cabinet (litres)

cylinder retainer on the sidewall, height adjustable without tools



30648 2

























Gas cylinder cabinet G-CLASSIC-30 model G30.205.090

in Light grey (RAL 7035), interior equipment with 1 x standard interior equipment for gas cylinders (sheet steel galvanised and powder coated)

Order No. 30673-001-30674 4

Technical data		G30.205.060
External dimensions W x D x H Internal dimensions W x D x H Weight without interior equip. Extraction air Air change 10 times Diff. pressure (air change 10 times) Air change 120 times Diff. pressure (air change 120 times) Distributed load Maximum load 50-litre gas cylinders	mm kg DN m³/h Pa m³/h Pa kg/m² kg	598 x 616 x 2050 494 x 479 x 1874 290 75 4 5 53 85 Pa 921 600
50-little gas cyllitaers	piece	2

Technical data		G30.205.090
External dimensions W x D x H	mm	898 x 616 x 2050
Internal dimensions W x D x H	mm	794 x 479 x 1874
Weight without interior equip.	kg	340
Extraction air	DN	75
Air change 10 times	m³/h	7
Diff. pressure (air change 10 times)	Pa	5
Air change 120 times	m³/h	86
Diff. pressure (air change 120 times)	Pa	147 Pa
Distributed load	kg/m²	648
Maximum load	kg	600
50-litre gas cylinders	piece	3

Safe and approved storage of flammable or toxic gases in working areas - for up to 3 x 50-litre gas cylinders

Function / construction:

- no unauthorised use: doors lockable with profile cylinder (integration in an existing locking system possible)
- easy alignment: adjusting aids to compensate for uneven
- easy mounting of connecting pipes and gas fittings: large interior height (1890 mm), many lead-through possibilities on the top of the cabinet
- ventilation: integrated air ducts ready for connection (DN 75) to a technical exhaust, even ventilation inside the cabinet

Available equipment

- standard interior equipment complete with mounting rails, rolling ramp, cylinder retainer and matching tension belts
- lateral cylinder retainer for two 10-litre cylinders, alternatively in height adjustable version (no tools required)
- cylinder retainer across the entire width of the cabinet











Gas cylinder cabinet G-CLASSIC-30 model G30.205.060

in Light grey (RAL 7035), interior equipment with 1 x standard interior equipment for gas cylinders (sheet steel galvanised and powder coated)


Order No. 30685-001-30687 4





G-CLASSIC-30 **◆ 090 / 60 cm ▶**



Selectional view








Earthing link Exhaust air DN 75 fresh air Ø75 230 334 1051 / 1136 Ø 21 (36x)

Top view



Order example - how to order correctly







2 door colours are available at no extra cost:

1x standard interior equipment for gas cylinders







Model	Information / equipment	Order No.
G30.205.090	without interior equipment	30673
G30.205.060	without interior equipment, left hinged	30685
G30.205.060.R	without interior equipment, right hinged	30686
Body colour	Door colour	Order No.
Light grey RAL 7035	Light grey RAL 7035	001 4

Walling yellow RAL 1004	Warning yellow RAL 1004		002 10
Interior equipment packages (can only be	e ordered in combination with the cabinet)	Material	Order No

Interior equipment packages (can only be ordered in combination with the cabinet) G30.205.060(R)		
G30.205.060(.R)	Material	Order No.

sheet steel galvanised and powder coated

G30.205.060(.R)	Material	Order No.	
1x standard interior equipment for gas cylinders	sheet steel galvanised and powder coated	30687 4	
		2)	

G30.205.090	Material	W x D x H (mm)	Kg L	Order No.
shelf	sheet steel powder-coated RAL 7035	782 x 337 x 25*	75.00	30675 🕗
grid, as storage level	steel galvanised	733 x 280 x 30	180.00	30789 4
Interior equipment G30.205.060(.R)	Material	W x D x H (mm)	1) (2)	3) Order No.
shelf	sheet steel powder-coated RAL 7035	482 x 337 x 25*	75.00	30688 🕗

Accessories	Order No.
cylinder retainer, profile as a cylinder retainer incl. 2 tension belts and mounting material flexible mounting in height at the rear wall	30650 🕗
cylinder retainer on the sidewall	30647 2
cylinder retainer on the sidewall, height adjustable without tools	30648 🕗
Ermeto coupling	5981 🕗
preparation for lead-through with female thread	30649 🕗
ension belt, additional	13181 🕗
gas cylinder trolley	26294 2

^{*} W x D usable storage space / 1) load capacity (kg), 2) capacity (litres), 3) maximum container volume inside the cabinet (litres)

